

Model	HD60B5TV100	HD60B5TF200	HD60B5TS200	HD60B5TSH200	HD60B5TK500	HD60B5TS500
Image Sensor	1/4" CMOS sensor	1/2.7" CMOS Sensor	1/2.8" CMOS Sensor	1/2.8" CMOS Sensor	1/2.7" CMOS Sensor	1/2.9" CMOS Sensor
Sensor Brand	OV	Silicon	Sony	Sony	Silicon	OV
HD Video output	AHD/CVI/TVI	AHD/CVI/TVI	AHD/CVI/TVI	AHD/CVI/TVI	AHD/CVI/TVI	AHD/CVI/TVI
Image Resolution	720P	1080P	1080P	1080P	5MP	5MP
OSD Menu	No	Yes	Yes	Yes	Yes	Yes
WDR	No	DWDR	DWDR	DWDR	DWDR	DWDR
Effective Pixels	1305(H)x977(V)	1930(H) × 1088(V)			2592(H) × 1944(V)	
TV System	PAL/NTSC					
S/N Ratio	More than 62 dB					
Scanning System	Progressive Scan					
Synchronization	Internal					
Noise Reduction	DNR	DNR	DNR	3D NR	DNR	DNR
White Balance	Auto/Manual					
Gain Control	Auto					
Picture Adjustment	Yes					
IR Features						
Infrared LED	Φ 5X72PCS					
Max. IR LEDs Length	60M					
IR Status	Under 10 Lux by CDS					
IR power on	CDS Auto Control					
Day/Night	IR cut filter with auto switch					
Lens						
Focal length	2.8-12mm (9-22mm is optional)					
Lens Type	Manual					
Mount Type	M12					
General						
Housing	Metal					
Bracket	Yes					
Waterproof	IP66					
Power Supply	DC12V					
Working Environment	-10°C~+50°C / 20%~95%RH					
Storage Temperature	-20°C ~ +60°C RH95% Max					
Dimensions(W×H×D)	295mm x 120mm x 103mm					
Weight	1.9kg					