

Model	NVR6TH32	
System	Main processor	Hi3535
	Operating System	Embedded Linux
	System resources	Simultaneous multi-channel real-time recording, playback, network operation, USB backup
Interface	Operator interface	16-bit true color graphic menu operation interface, support mouse operation
	Preview	1/4/8/16/24/32
Video	Video input (IP)	32CH*1080P/16CH*4MP/8CH*5MP
	Video standards	PAL(625TVL,50f/s); NTSC(525TVL,60f/s)
	Video compression	H.264
	Display quality	Max 1920*1080
	Playback quality	4CH*1080P/4CH*4MP/2CH*5MP
	Motion detection	Support(depend on camera)
Audio	Audio compression	G.711A
	Intercom	Support
Record	Recording mode	Manual>Alarm>Dynamic Detection>Timing
	Search mode	Search by Time/Calendar/Event/Channel
Storage & Backup	Space occupation	Video: CIF 4~5G/day*channel, D1 8~10G/day*channel; 960H 12G~20G/day*channel
		720P 20~30G/day*channel; 1080P ~40G/day*channel; Audio: 691.2M/day*channel
	Record storage	HDD、 Network
	Backup mode	Network backup, USB hard disk, USB burner, SATA burner
External interface	Video output	1ch VGA, 1ch HDMI HD output
	Audio I/O	1/1
	Alarm I/O	16/4
	Network interface	1*RJ45 10M/100M/1000M Adaptive Ethernet port
	USB interface	2*USB2.0 ports (reserve 2 front ports)
	HDD	4 SATA(Up to 8TB for each disk) ,1*ESATA
General	PTZ control	Control PTZ device by network
	ONVIF	Support
	Power supply	12V/6A
	Power Consumption	<10W(Without HDD)
	Work environment	Temperature:0°C- + 55°C , Humidity:10% - 90%RH , Atm:86kpa - 106kp
	Dimension	375*55*220MM
	Weight	Around 3.5kg